

Huaxing lithium iron phosphate battery pack for golf cart

Huaxing designed 48V and 72V lithium iron phosphate battery pack replace the lead-acid battery which are available for drop-in replacement in the Club Car and EZ-GO etc. vehicles

Huaxing offers lithium-iron battery solutions for low-speed vehicles including golf carts, AGV, forklifts, aerial work platforms and floor cleaning machines, as well as renewable energy storage systems including residential, commercial & industrial, marine applications.

Model	HX48100	HX4884	HX4878	HX72100
Rated Voltage	51.2V	51.2V	51.2V	76.8V
Rated Capacity	100Ah	84AH	78AH	100AH
Dimension(mm)	500*343*256.5	526*324*258.2	526*324*258.2	805*333*254.5
Weight(kg)	60	45	43	85
Cycle life	over 3500 times			
IP grade	IP65			
Operation Temperature	-20~60°C			
Housing material	Steel case			
Protection function	Software BMS,RS485 short circuit, over charge, over discharge, over current, over temperature			



HX 48V 100AH lithium ion battery pack for golf cart

XUAXING

华兴新能源



Battery Parameter	51.2V100Ah
Rated Voltage(V)	51.2V
Rated CapacityAh)	100Ah
Charge temperature (°C)	0-45
Dishcharge temperature (°C)	-20-60
Charge time (h)	4-5
IP grade	IP65
Dimension (mm)	500*343*256.5 (not include handle)
Weight(kg)	60

HX 51.2V 84AH lithium ion battery pack for golf cart



Battery Parameter	51.2V84Ah
Rated Voltage(V)	51.2
Rated Capacity(Ah)	84
Charge temperature (°C)	0-45
Discharge temperature (°C)	-20-60
Charge and discharge current (A)	84
IP grade	IP65
Dimension (mm)	526*324*258.2
Weight (kg)	45
Case material	Steel case

HX 51.2V 78AH lithium ion battery pack for golf cart



Battery Parameter	51.2V78Ah
Rated Voltage(V)	51.2
Rated Capacity(Ah)	78
Charge temperature (°C)	0-45
Discharge temperature (°C)	-20-60
Charge and discharge current (A)	78
IP grade	IP65
Dimension (mm)	526*324*258.2
Weight (kg)	43
Case material	Steel case

HX 76.8V 100AH lithium ion battery pack for golf cart



Battery Parameter	76.8V100Ah
Rated Voltage(V)	76.8
Rated Capacity(Ah)	100
Charge temperature (°C)	0-60
Discharge temperature (°C)	-20-60
Charge and discharge current (A)	100
IP grade	IP65
Dimension (mm)	805*333*254.5
Weight (kg)	85
Case material	Steel case